



Standardowe koła do pasów zębatych typu HTD pod tuleje Taper Lock®

Podziałka 8 mm



TL ...8 M 20

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Materiał
TL 22 - 8 M 20	22	4	56,02	54,65	62	38	28	-	6	22	1008	Z FLANSZAMI	ZELIWO
TL 24 - 8 M 20	24	4	61,12	59,74	67	42	28	-	6	22	1008		
TL 26 - 8 M 20	26	4	66,21	64,84	73	45	28	-	6	22	1008		
TL 28 - 8 M 20	28	4	71,30	69,93	77	52	28	-	6	22	1008		
TL 30 - 8 M 20	30	4	76,39	75,02	84	56	28	-	6	22	1008		
TL 32 - 8 M 20	32	4	81,49	80,12	88	65	28	-	3	25	1610		
TL 34 - 8 M 20	34	4	86,58	85,21	94	66	28	-	3	25	1610		
TL 36 - 8 M 20	36	4	91,67	90,30	98	68	28	-	3	25	1610		
TL 38 - 8 M 20	38	4	96,77	95,39	104	76	28	-	3	25	1610		
TL 40 - 8 M 20	40	4	101,86	100,49	108	80	28	-	3	25	1610		
TL 44 - 8 M 20	44	1	112,05	110,67	121	-	28	99	4	32	2012		
TL 48 - 8 M 20	48	1	122,23	120,86	129	-	28	105	4	32	2012		
TL 56 - 8 M 20	56	1	142,60	141,23	149	-	28	105	4	32	2012		
TL 64 - 8 M 20	64	6	162,97	161,60	168	140	28	110	4	32	2012		
TL 72 - 8 M 20	72	6	183,35	181,97	191	158	28	110	4	32	2012		
TL 80 - 8 M 20	80	9	203,72	202,35	-	178	28	110	4	32	2012		
TL 90 - 8 M 20	90	12	229,18	227,81	-	204	28	110	4	32	2012		





TL ...8 M 30

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Materiał
TL 22 - 8 M 30	22	4	56,02	54,65	62	38	38	-	16	22	1008	Z FLANSZAMI	ZELIWO
TL 24 - 8 M 30	24	4	61,12	59,74	67	42	38	-	16	22	1008		
TL 26 - 8 M 30	26	4	66,21	64,84	73	45	38	-	16	22	1008		
TL 28 - 8 M 30	28	4	71,30	69,93	77	52	38	-	16	22	1008		
TL 30 - 8 M 30	30	8	76,39	75,02	84	-	38	-	-	38	1615		
TL 32 - 8 M 30	32	8	81,49	80,12	88	-	38	-	-	38	1615		
TL 34 - 8 M 30	34	8	86,58	85,21	94	-	38	-	-	38	1615		
TL 36 - 8 M 30	36	8	91,67	90,30	98	-	38	-	-	38	1615		
TL 38 - 8 M 30	38	8	96,77	95,39	104	-	38	-	-	38	1615		
TL 40 - 8 M 30	40	8	101,86	100,49	108	-	38	-	-	38	1615		
TL 44 - 8 M 30	44	2	112,05	110,67	121	90	38	-	3	32	2012		
TL 48 - 8 M 30	48	2	122,23	120,86	129	96	38	-	3	32	2012		
TL 56 - 8 M 30	56	2	142,60	141,23	149	118	38	-	3	32	2012		
TL 64 - 8 M 30	64	6	162,97	161,60	168	140	38	115	7	45	2517		
TL 72 - 8 M 30	72	6	183,35	181,97	191	158	38	120	7	45	2517		
TL 80 - 8 M 30	80	9	203,72	202,35	-	178	38	120	7	45	2517		
TL 90 - 8 M 30	90	12	229,18	227,81	-	204	38	120	7	45	2517		
TL 112 - 8 M 30	112	12	285,21	283,83	-	260	38	120	7	45	2517		
TL 144 - 8 M 30	144	12	366,69	365,32	-	341	38	120	7	45	2517		




TL ...8 M 50

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Materiał
TL 28 - 8 M 50	28	2	56,02	69,93	77	52	60	-	19	22	1008	Z FLANSZAMI	ZELIWO
TL 30 - 8 M 50	30	4	61,12	75,02	84	58	60	-	22	38	1615		
TL 32 - 8 M 50	32	4	81,49	80,12	88	60	60	-	22	38	1615		
TL 34 - 8 M 50	34	4	86,58	85,21	94	66	60	-	22	38	1615		
TL 36 - 8 M 50	36	4	91,67	90,30	98	68	60	-	22	38	1615		
TL 38 - 8 M 50	38	4	96,77	95,39	104	75	60	-	22	38	1615		
TL 40 - 8 M 50	40	2	101,86	100,49	108	80	60	-	14	32	2012		
TL 44 - 8 M 50	44	2	112,05	110,67	121	90	60	-	14	32	2012		
TL 48 - 8 M 50	48	2	122,23	120,86	129	100	60	-	14	32	2012		
TL 56 - 8 M 50	56	2	142,60	141,23	149	120	60	-	7,5	45	2517		
TL 64 - 8 M 50	64	5	162,97	161,60	168	138	60	115	7,5	45	2517		
TL 72 - 8 M 50	72	5	183,35	181,97	191	158	60	120	7,5	45	2517		
TL 80 - 8 M 50	80	7	203,72	202,35	-	178	60	140	4,5	51	3020		
TL 90 - 8 M 50	90	7	229,18	227,81	-	204	60	146	4,5	51	3020		
TL 112 - 8 M 50	112	14	285,21	283,83	-	260	60	146	4,5	51	3020		
TL 144 - 8 M 50	144	14	366,69	365,32	-	341	60	146	4,5	51	3020		
TL 168 - 8 M 50	168	14	427,80	426,42	-	402	60	146	4,5	51	3020		
TL 192 - 8 M 50	192	14	488,92	487,54	-	462	60	146	4,5	51	3020		



TL ...8 M 85



Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-iał
TL 34 - 8 M 85	34	2	86,58	85,21	94	66	95	-	28,5	38	1615	Z FLANSZAMI	ŻELIWO
TL 36 - 8 M 85	36	2	91,67	90,30	98	68	95	-	28,5	38	1615		
TL 38 - 8 M 85	38	2	96,77	95,39	104	75	95	-	28,5	38	1615		
TL 40 - 8 M 85	40	2	101,86	100,49	108	80	95	-	31,5	32	2012		
TL 44 - 8 M 85	44	2	112,05	110,67	121	90	95	-	31,5	32	2012		
TL 48 - 8 M 85	48	2	122,23	120,86	129	100	95	-	25	45	2517		
TL 56 - 8 M 85	56	2	142,60	141,23	149	120	95	-	25	45	2517		
TL 64 - 8 M 85	64	2	162,97	161,60	168	138	95	-	25	45	2517		
TL 72 - 8 M 85	72	2	183,35	181,97	191	158	95	-	22	51	3020		
TL 80 - 8 M 85	80	7	203,72	202,35	-	178	95	140	22	51	3020		
TL 90 - 8 M 85	90	7	229,18	227,81	-	204	95	146	22	51	3020		
TL 112 - 8 M 85	112	14	285,21	283,83	-	260	95	146	22	51	3020		
TL 144 - 8 M 85	144	14	366,69	365,32	-	341	95	140	9,5	76	3030		
TL 168 - 8 M 85	168	14	427,80	426,42	-	402	95	140	9,5	76	3030		
TL 192 - 8 M 85	192	14	488,92	487,54	-	462	95	140	9,5	76	3030		



Podziałka 14 mm



TL ...14 M 40

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-iał
TL28 - 14 M 40	28	2	124,78	122,12	134	98	54	-	11	32	2012	Z FLANSZAMI	ŻELIWO
TL29 - 14 M 40	29	2	129,23	126,57	134	100	54	-	11	32	2012		
TL30 - 14 M 40	30	2	133,69	130,99	142	100	54	-	11	32	2012		
TL32 - 14 M 40	32	2	142,60	139,88	150	104	54	-	11	32	2012		
TL34 - 14 M 40	34	2	151,52	148,79	158	110	54	-	4,5	45	2517		
TL36 - 14 M 40	36	2	160,43	157,68	166	120	54	-	4,5	45	2517		
TL38 - 14 M 40	38	2	169,34	166,60	177	130	54	-	4,5	45	2517		
TL40 - 14 M 40	40	2	178,25	175,49	186	138	54	-	4,5	45	2517		
TL44 - 14 M 40	44	2	196,08	193,28	209	154	54	-	1,5	51	3020		
TL48 - 14 M 40	48	2	213,90	211,11	216	172	54	-	1,5	51	3020		
TL56 - 14 M 40	56	5	249,56	246,76	261	207	54	146	1,5	51	3020		
TL64 - 14 M 40	64	5	285,21	282,41	288	243	54	146	1,5	51	3020		
TL72 - 14 M 40	72	7	320,86	318,06	-	279	54	146	1,5	51	3020		
TL80 - 14 M 40	80	14	356,51	353,71	-	314	54	146	1,5	51	3020		
TL90 - 14 M 40	90	14	401,07	398,28	-	359	54	146	1,5	51	3020		
TL112 - 14 M 40	112	14	499,11	496,32	-	457	54	146	1,5	51	3020		
TL144 - 14 M 40	144	14	641,71	638,92	-	600	54	146	1,5	51	3020		
TL168 - 14 M 40	168	14	748,66	745,87	-	705	54	146	1,5	51	3020		
TL192 - 14 M 40	192	12	855,62	852,82	-	812	54	178	35	89	3535		
TL216 - 14 M 40	216	12	962,57	959,77	-	920	54	178	35	89	3535		
TL264 - 14 M 40	264	12	1176,47	1173,67	-	1133	54	178	35	89	3535		




TL ...14 M 55

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-iał
TL28 - 14 M 55	28	2	124,78	122,12	134	98	70	-	19	32	2012	Z FLANSZAMI	ŻELIWO
TL29 - 14 M 55	29	2	129,23	126,57	134	100	70	-	19	32	2012		
TL30 - 14 M 55	30	2	133,69	130,99	142	100	70	-	12,5	45	2517		
TL32 - 14 M 55	32	2	142,60	139,88	150	104	70	-	12,5	45	2517		
TL34 - 14 M 55	34	2	151,52	148,79	158	110	70	-	12,5	45	2517		
TL36 - 14 M 55	36	2	160,43	157,68	166	120	70	-	12,5	45	2517		
TL38 - 14 M 55	38	2	169,34	166,60	177	130	70	-	12,5	45	2517		
TL40 - 14 M 55	40	2	178,25	175,49	186	138	70	-	12,5	45	2517		
TL44 - 14 M 55	44	2	196,08	193,28	209	154	70	-	9,5	51	3020		
TL48 - 14 M 55	48	2	213,90	211,11	216	172	70	-	9,5	51	3020		
TL56 - 14 M 55	56	5	249,56	246,76	261	207	70	146	9,5	51	3020		
TL64 - 14 M 55	64	5	285,21	282,41	288	243	70	146	9,5	51	3020		
TL72 - 14 M 55	72	7	320,86	318,06	-	279	70	146	9,5	51	3020		
TL80 - 14 M 55	80	14	356,51	353,71	-	314	70	146	9,5	51	3020		
TL90 - 14 M 55	90	14	401,07	398,28	-	359	70	146	9,5	51	3020		
TL112 - 14 M 55	112	14	499,11	496,32	-	457	70	146	9,5	51	3020		
TL144 - 14 M 55	144	14	641,71	638,92	-	600	70	146	9,5	51	3020		
TL168 - 14 M 55	168	14	748,66	745,87	-	705	70	146	9,5	51	3020		
TL192 - 14 M 55	192	12	855,62	852,82	-	812	70	178	19	89	3535		
TL216 - 14 M 55	216	12	962,57	959,77	-	920	70	178	19	89	3535		
TL264 - 14 M 55	264	12	1176,48	1173,67	-	1133	70	178	19	89	3535		




TL ...14 M 85

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-ial
TL28 - 14 M 85	28	2	124,78	122,12	134	98	102	-	28,5	45	2517	Z FLANSZAMI	ŻELIWO
TL29 - 14 M 85	29	2	129,23	126,57	134	100	102	-	28,5	45	2517		
TL30 - 14 M 85	30	2	133,69	130,99	142	100	102	-	28,5	45	2517		
TL32 - 14 M 85	32	2	142,60	139,88	150	104	102	-	28,5	45	2517		
TL34 - 14 M 85	34	2	151,52	148,79	158	110	102	-	28,5	45	2517		
TL36 - 14 M 85	36	2	160,43	157,68	166	120	102	-	25,5	51	3020		
TL38 - 14 M 85	38	2	169,34	166,60	177	130	102	-	25,5	51	3020		
TL40 - 14 M 85	40	2	178,25	175,49	186	138	102	-	25,5	51	3020		
TL44 - 14 M 85	44	2	196,08	193,28	209	154	102	-	13	76	3030		
TL48 - 14 M 85	48	2	213,90	211,11	216	172	102	-	13	76	3030		
TL56 - 14 M 85	56	2	249,56	246,76	261	207	102	-	6,5	89	3535		
TL64 - 14 M 85	64	5	285,21	282,41	288	243	102	178	6,5	89	3535		
TL72 - 14 M 85	72	7	320,86	318,06	-	279	102	178	6,5	89	3535		
TL80 - 14 M 85	80	14	356,51	353,71	-	314	102	178	6,5	89	3535		
TL90 - 14 M 85	90	14	401,07	398,28	-	359	102	178	6,5	89	3535		
TL112 - 14 M 85	112	14	499,11	496,32	-	457	102	178	6,5	89	3535		
TL144 - 14 M 85	144	14	641,71	638,92	-	600	102	178	6,5	89	3535		
TL168 - 14 M 85	168	14	748,66	745,87	-	705	102	178	6,5	89	3535		
TL192 - 14 M 85	192	14	855,62	852,82	-	812	102	215	-	102	4040		
TL216 - 14 M 85	216	14	962,57	959,77	-	920	102	215	-	102	4040		
TL264 - 14 M 85	264	14	1176,47	1173,67	-	1133	102	215	-	102	4040		



TL ...14 M 115

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-ial
TL28 - 14 M 115	28	2	124,78	122,12	134	98	133	-	44	45	2517	Z FLANSZAMI	ŻELIWO
TL29 - 14 M 115	29	2	129,23	126,57	134	100	133	-	44	45	2517		
TL30 - 14 M 115	30	2	133,69	130,99	142	100	133	-	44	45	2517		
TL32 - 14 M 115	32	2	142,60	139,88	150	104	133	-	44	45	2517		
TL34 - 14 M 115	34	2	151,52	148,79	158	110	133	-	44	45	2517		
TL36 - 14 M 115	36	2	160,43	157,68	166	120	133	-	41	51	3020		
TL38 - 14 M 115	38	2	169,34	166,60	177	130	133	-	41	51	3020		
TL40 - 14 M 115	40	2	178,25	175,49	186	138	133	-	41	51	3020		
TL44 - 14 M 115	44	2	196,08	193,28	209	154	133	-	28,5	76	3030		
TL48 - 14 M 115	48	2	213,90	211,11	216	172	133	-	28,5	76	3030		
TL56 - 14 M 115	56	2	249,56	246,76	261	207	133	-	22	89	3535		
TL64 - 14 M 115	64	5	285,21	282,41	288	243	133	178	22	89	3535		
TL72 - 14 M 115	72	7	320,86	318,06	-	279	133	178	22	89	3535		
TL80 - 14 M 115	80	14	356,51	353,71	-	314	133	178	22	89	3535		
TL90 - 14 M 115	90	14	401,07	398,28	-	359	133	178	22	89	3535		
TL112 - 14 M 115	112	14	499,11	496,32	-	457	133	178	22	89	3535		
TL144 - 14 M 115	144	14	641,71	638,92	-	600	133	215	15,5	102	4040		
TL168 - 14 M 115	168	14	748,66	745,87	-	705	133	215	15,5	102	4040		
TL192 - 14 M 115	192	14	855,62	852,82	-	812	133	215	15,5	102	4040		
TL216 - 14 M 115	216	14	962,57	959,77	-	920	133	215	15,5	102	4040		
TL264 - 14 M 115	264	14	1176,47	1173,67	-	1133	133	267	3	127	5050		



TL ...14 M 170

Kod	Ilość zębów	typ	R mm Ø	S mm Ø	e mm Ø	U mm	W mm	H mm Ø	Z mm	Y mm	Taper Lock	Flan-sze	Mater-ial
TL38 - 14 M 170	38	2	169,34	166,60	177	130	187	-	55,5	76	3030	Z FLANSZAMI	ŻELIWO
TL40 - 14 M 170	40	2	178,25	175,49	186	138	187	-	55,5	76	3030		
TL44 - 14 M 170	44	2	196,08	193,28	209	154	187	-	49	89	3535		
TL48 - 14 M 170	48	2	213,90	211,11	216	172	187	-	49	89	3535		
TL56 - 14 M 170	56	2	249,56	246,76	261	207	187	-	49	89	3535		
TL64 - 14 M 170	64	2	285,21	282,41	288	243	187	-	42,5	102	4040		
TL72 - 14 M 170	72	7	320,86	318,06	-	279	187	215	42,5	102	4040		
TL80 - 14 M 170	80	7	356,51	353,71	-	314	187	215	42,5	102	4040		
TL90 - 14 M 170	90	14	401,07	398,28	-	359	187	215	42,5	102	4040		
TL112 - 14 M 170	112	14	499,11	496,32	-	457	187	267	30	127	5050		
TL144 - 14 M 170	144	14	641,71	638,92	-	600	187	267	30	127	5050		
TL168 - 14 M 170	168	14	748,66	745,87	-	705	187	267	30	127	5050		
TL192 - 14 M 170	192	14	855,62	852,82	-	812	187	267	30	127	5050		
TL216 - 14 M 170	216	14	962,57	959,77	-	920	187	267	30	127	5050		
TL264 - 14 M 170	264	14	1176,47	1173,67	-	1133	187	267	30	127	5050		

